

Rex-Royal S1 CTH









# Rex-Royal S1 CTH

The S1 CTH model has a tea/steam boiler in addition to the coffee boiler. This increases the hourly hot water output to as much as 26 litres, and hot water can even be dispensed at the same time as the coffee products. The speciality coffees can also be prepared as double servings in this model. The optionally available heated coffee spout also guarantees a hot espresso at all times — even when there are interruptions to the supply or when the machine is left standing for relatively long periods of time.

### **Features**



T- Hot Water



C- Coffee

# Advantages

### High-quality metal brewing unit

Premium coffee quality thanks to the high-quality, more powerful Rex-Royal metal brewing unit with a capacity of 16 grams of ground coffee per brewing operation

### 26 I/h hot water supply

Hot water supply at a rate of up to 26 litres per hour

### Intuitive menu navigation

Simple to run and maintain thanks to visual user prompts and automatic cleaning

# Short maintenance times

Modular construction for short intervention and maintenance times for a long-term and secure investment

## Add-On units

With options like cup warmers, cup dispensers and mobile solutions, the Rex-Royal coffee machines are perfectly suited to meet your requirements

# Simultaneous dispensing of hot water and two coffee products

Possible to simultaneously supply hot water and coffees, even as a double product

### Video-capable 7-inch TouchScreen

Intuitive menu navigation thanks to the 7-inch touch screen for the simple and efficient selection of a drink

### Sales promotion on TouchScreen

Place advertising messages and ambient images on the display

# Heated coffee outlet

With the optional heated coffee spout, a perfect, hot espresso is guaranteed, even if the machine isn't used for a long time

### Highest hygiene standards

Automatic, HACCP-certified cleaning process guarantees the machine will run in a perfectly hygienic way with minimal time expenditure

# Specifications

## General

Rating	220-240V- 50/60 Hz   380-415V- 50/60 Hz
Power	1.9-2.3 kW   3.8-4.2 kW
Water hot	25 l/h   26 l/h
Weight	43.6 kg
Width / Height / Depth	310 mm / 635 mm / 599 mm